IDEL 3475 LED

6-LED No-Air Polyurethane-Wrapped Aluminum Blast Light











Optional Battery Clamps

	Product Features
Light Output:	1,200 Lumens
Brightness:	>40,000 Lux @ 1 foot with Optics
Beam:	25° (Spot Light)
Optics:	Refractive Optic Design
Light Source:	LED
Color Temperature:	6000K (+/-200K)
Power Consumption:	18 Watts
Voltage Options:	12-28V AC/DC
	220 V AC
Housing:	Light Body: Aluminum
	Handle: Polyurethane
	Halo: Shock-absorbing polyurethane
Dimensions:	7" Length x 3.0" Diameter
Weight:	Lighthead: ~2.0 lbs
	100' System: ~8.5 lbs
Cable Options:	100' Extreme Cable (standard)
	Other lengths available (min. 10 feet)
	Battery Clamp option available (10 ft - Min. Cord Length)
No Air:	Yes
Replacement Accessories & Parts: (See Diagram Page)	[3402 LED-3] Replacement Halo
	[3609B] Pyrex Blast Lens (Box of 12)
	[3475 CR Lens Pk] Polycarbonate Lens (12 pk w/ screws)
	[3112HC-LED] Light Stanchion & Hose Clamp







