

# MODEL 7453 LED

## Intrinsically Safe Yellow Dual-Light Flashlight


FLASHLIGHTS  
& HEADLAMPS

**INTRINSICALLY SAFE**

February 2017

### Product Features

|                             |   |
|-----------------------------|---|
| <b>Safety Ratings:</b>      | Class I, Division 1 Groups A, B, C, D; T3<br>Class II & III Groups E, F, G; T135C<br>Class I, Zone 0 AEX ia IIC; T3 Ga<br>Class I, Zone 0 EX ia IIC; T3 Ga  |
| <b>Conforms to:</b>         | ANSI/UL STD 913<br>ANSI/UL 60079-0<br>ANSI/UL 60079-11<br>ANSI/UL 60079-26  |
| <b>Certified to:</b>        | CAN/CSA STD C22.2 NO 157<br>CAN/CSA STD C22.2 NO 60079-0<br>CAN/CSA STD C22.2 NO 60079-11<br>CSA STD C22.2 NO 25  |
| <b>Approvals:</b>           | cETLus, ATEX, IECEx & MSHA listed intrinsically safe permissible  |
| <b>Emitter Type:</b>        | CREE LED (50K hour lifetime)  |
| <b>Light Output:</b>        | Spotlight: 120 lumens, 17.5 h runtime<br>Floodlight: 120 lumens, 17.5 h runtime<br>Dual-Light: 240 lumens, 4.5 h runtime  |
| <b>Candela:</b>             | 7,250 cd (peak beam intensity)  |
| <b>Power:</b>               | 3 "AA" Premium Batteries (Not Included)   |
| <b>Body:</b>                | Engineered polymer housing w/ Non-slip grip   |
| <b>Dimensions:</b>          | 7" L x 1.5"-1.1" Diameter (Handle)  |
| <b>Light Head Diameter:</b> | 1.8" Diameter   |
| <b>Switch:</b>              | Dual push-button controls   |
| <b>Special Features:</b>    | 2m drop rating<br>Water-Proof<br>Impact & Chemical resistant<br>Permissible for use in both above and below ground hazardous locations where explosive gases and dust may be<br>Dual-Light (spot & wide-area light use at the same time) for maximum versatility. |



| FL1 STANDARD | SPOT/FLOOD        | DUAL-LIGHT        |
|--------------|-------------------|-------------------|
|              | <b>120 LUMENS</b> | <b>240 LUMENS</b> |
|              | <b>17.5 HOURS</b> | <b>4.5 HOURS</b>  |
| <br>7250cd   | <br>170m          | <br>1m            |
|              | <br>2m            |                   |



Western Technology, Inc. Toll Free: (800) 654-5483  
3517 Arsenal Way Local: (360) 917-0080  
Bremerton, WA 98312 Fax: (360) 917-0083  
[www.WesternTechnologyLights.com](http://www.WesternTechnologyLights.com)