

## COBRA™ 212

### Release Agent

**COBRA™ 212** is a ready to use flammable release agent that can be used in a wide variety of core making operations. Manufactured with high quality ingredients, **COBRA™ 212** provides excellent lubrication and release with minimal build up on the pattern. Practical areas of use include processes that disallow water-containing products and when flammability is not a concern.

### Features

- Wide Variety of Applications
- No Montreal Protocol Regulations
- Excellent Release
- A Moderately Fast Evaporation Rate of the Carrier
- Economical

### Typical Product Data

(These values are not intended for use in preparing specifications)

Flash Point (C.O.C.)	100° F.
Evaporation Rate	0.2 (Butyl Acetate = 1 )
Active Content	11 %
Freeze Point	Less Than 32° F.
Density (lbs./gal.)	6.8

### Use Recommendations

**COBRA™ 212** has seen usage and success in the areas of Catalyzed Resin/Sand Molding. The release will be affected by usage rates and intricacy of the core produced. Generally, the release agent can be applied using conventional spraying equipment such as an airless sprayer, a pressurized canister type sprayer or a molder's mouth sprayer. In the latter instance it may be necessary to reduce the airflow in the inlet orifice of the container. Due to the flammability of **COBRA™ 212**, care should be taken when handling and applying this product.