

DOWNTRON DFF SERIES

Dust Collector/Downdraft Tables



Industrial Downdraft Tables

What Industry Needs in a Downdraft Table

A Size That Fits the Application

From single-station to multi-operation, every Downtron is sized to fit the need, whether meeting stringent space requirements or accommodating multiple workers and/or large pieces.

Rugged Construction Combined With Quiet, Energy-Efficient Operation

The DFF Series is built of heavy-sheet steel and rolled structural shapes in an all-welded cabinet. Direct drive, backward-inclined airfoil type blowers have coned inlets and sound-insulated housing. With a standard rating of 78DB or lower, the Downtron may also be equipped with an optional blower exhaust stack silencer.

High-Efficiency/Large Capacity Cartridge Filters with Automatic Cleaning

Rated at 99.9% efficient in the capture of particles 0.5 microns and larger, the Downtron's film-laminated media provides consistent high efficiency, as well as easy release of the dust cake in the cleaning cycle. The power-pulse cleaning system uses a solid-state controller to automatically sequence the pulse valves during the off-line cleaning cycle.

Why a Self-Contained Downdraft Table?

Broad Spectrum Collection

Works with gravity to collect a wide range of dust particles.

Worker Ease

Freedom of movement for the operator, as compared to arms or vacuum attachments.

Accessibility

Provides a work cell wherever needed in the shop.

Various Size Tasks

One or more operators, working on small or large pieces.

Space Economy

Compact dust collector / work table configuration.

Energy Savings

Re-circulation of filtered air.



FILTER 1

1-800-289-0189

CUSTOM SPECIALISTS FOR INDUSTRIAL NEEDS

DOWNTRON DFF SERIES

Downdraft Table With Integral Cartridge Dust Collector



High-Efficiency Dust Collection Table Sized to Fit the Need

Features

- 99.9% Efficient Filters (0.5 microns and larger) with 8//20 Media Blend of Manmade/Natural Fibers, Laminated w/ Blow Melt Polypropylene with a UL Class 2 Fire Retardent Treatment
- Three Phase TEFC Motors on Rubber Vibration Mounts
- Direct Drive, Backward Inclined Airfoil Type Blower with Coned Inlet for Maximum Efficiency
- Sound Rating of Maximum 78 DB
- All Welded 12/14 Ga. Steel
- No Bearings to Grease or Belts to Change
- Pull-Out Dust Drawers
- Automatic Power-Pulse Filter Cleaning
- Grated Downdraft Work Surface
- Industrial Blue Enamel

Typical Applications

Contaminants: Light to Heavy Dust, Soldering Smoke, Powders, Dry Chemicals

Processes

- Sanding / Grinding
- Soldering
- Chemical Mixing
- Finishing
- Deburring
- Buffing

Options

- Carbon After Filters
- Odor Absorption Modules
- Sound Attenuators
- Safety After Filters--Ashrae or HEPA
- Work Surface Grating: Metal, Galvanized, Stainless Steel, Non-Scratch Fiberglass, Rubber, Wood; Various Hole Size
- Safety Monitor Gauge and Alarm
- Motor Starters and Electrical Disconnects with Transformer for Cleaning Circuit Control and Lighting
- Auxiliary Air and Power Outlets
- High Temperature Cut-Off of Blower
- Sprinkler Heads
- Application-Specific Filter Media
- Casters: +2" to Height

Downtron DFF Series				
MODEL	CFM	Blower		Filter SQ FT
		HP	D x W* H = 36" STD	
DFF-3-1-1.5	1,200	1.5	38" x 32"	275
DFF-3-3-3	4,000	3	40" x 36"	825
DFF-56-4-3	4,000	3	48" x 56"	1,100
DFF-6-6-5-40	6,000	5	40" x 72"	1,380
DFF-6-6-5	6,000	5	48" x 72"	1,650
DFF-8-8-5	6,000	5	48" x 96"	2,200
DFF-8-8-7.5	8,000	7.5	48" x 96"	2,200
DFF-8-8-5-5W	6,000	5	60" x 96"	2,200
DFF-10-8-5	6,000	5	48" x 120"	2,200
DFF-10-8-7.5	8,000	7.5	48" x 120"	2,200
DFF-10-10-7.5	8,000	7.5	48" x 120"	2,750
DFF-12-14-7.5	8,000	7.5	72" x 144"	3,850

*Larger/Custom Sizing Available: Consult Factory

Filter 1 has a policy of continuous design improvement and reserves the right to update designs and specifications without notice.

FILTER 1

2525 National Dr.
Garland, TX 75041
972-278-2664

WWW.FILTER-1.COM