

MODEL 7403

HID Explosion Proof Rechargeable Flashlight

February 2017

Optional Lens Filters:



UV405nm



UV365nm



Product Features

Approved for:	<i>Class I, Division 1, Groups A, B, C, D Class I, Division 2, Groups A, B, C, D Class II, Division 1, Groups E, F, G Class II, Division 2, Groups E, F, G</i>
Conforms to:	<i>IP68 Waterproof to 3 Meters</i>
Temperature Rating:	<i>T-code: T4A</i>
Lamp Type:	<i>Xenide HID Bulb</i>
HID Life Expectancy:	<i>2,500 hours</i>
Color Temperature:	<i>6,500 K (Cool White)</i>
Rated with Optics:	<i>1,200 Lumens</i>
Brightness:	<i>5,1400 Lux @ 10 ft.</i>
Power Consumption:	<i>20 Watts</i>
Ambient Temp Range:	<i>-32° C to +45°C</i>
Dimensions:	<i>11.5" L</i>
Weight:	<i>1.9 lbs</i>
Material/Construction:	<i>Aluminum Housing</i>
Lighting Configuration:	<i>Spot</i>
Charging Unit:	<i>100/240VAC 50/60Hz w/ overcharge protection, LED indicator</i>
Battery:	<i>2600mAh Lithium Ion Battery</i>
Run-Time:	<i>90 Minutes</i>

Complete Kit Includes:

- HID XP Recharge Flashlight
- AC Battery Charger (LED Indicator)
- Molded Travel Case
- Straps Mounts
- Shoulder Strap
- Rubber Lens Cover & End Caps
- Lens Cleaning Cloth
- User's Manual

