

# WETBLAST FLEX™

## ALL-IN-ONE WETBLAST SYSTEM

Our all-in-one WETBLAST FLEX™ system gives you convenience you don't get from traditional slurry systems. Its design and simplified set up and operation make for easier end-of-shift shutdown. By mixing the abrasive and water after it leaves the blast machine, you never have to empty a machine of a messy water/abrasive mix.

Flexible set up options allow you to position the water injector either at the base of the blast machine or at the nozzle – your choice. With the injector at the nozzle, you can adjust the water/abrasive mix at any time.

You can dry-blast with the FLEX, simply remove the injector adaptor mounted at the base of the machine, and turn off air to the pump.



### SKID MOUNTED

All-in-one convenient design with fork lift pockets and lifting eyes.



### WATER SOURCE

On board water tank or municipal water source – add rust inhibitor if needed.



### ABRASIVE CUT OFF SWITCH

With injector and ACS at the nozzle, you can control wash down and surface blow off without a trip to the blast machine.



### NO POT TENDER NEEDED

With the injector adaptor and ACS mounted at the nozzle, there's no need for a pot tender.



## FLEX - \*BASE UNIT

6 ft<sup>3</sup> Blast Machine with Pneu Remotes and 50 ft Control Line

120 Gallon Water Tank

Wetblast Injector™ Pump Module

Base-Mount Wetblast Injector™

Standard Wetblast Injector™ with 50' Hose

Abrasive Cut-Off Switch

Blast Machine Screen & Cover

1 ½" Pressure Regulator & Air Filter

\*Contractor Thread : Stock No. 28434

\*1-1/4" Thread: Stock No. 28436

## FLEX - PACKAGE

Base Unit

50' Coupled Supa Hose

#8 Long-Venturi Nozzle

Nominal Spares

\*Contractor Thread : Stock No. 28435

\*1-1/4" Thread: Stock No. 28437

Dimensions: 68" L x 46" W x 52" H

Base Weight: 1450 LBS

Package Weight: 1550 LBS

Apollo 600 HP DLX

Clem-Cool Air Conditioner

CPF-20 (installed on skid)

50' Respirator Hose

\* Systems differ with choice of nozzle injector adaptor – contractor or fine thread.

